



SAFETY DATA SHEET

Page 1 of 7
SW-1237-Z

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards



SDS Revision: 1.0

SDS Revision Date: 5/5/2015

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	HEALING STYLE DESIGN FOAM, 6% VOC
1.2	Chemical Name:	Aerosol
1.3	Synonyms:	SW-1237-Z
1.4	Trade Names:	Healing Style Design Foam, 6% VOC
1.5	Product Uses & Restrictions:	Aerosol Hair Mousse
1.6	Distributor's Name:	Shield Packaging of CA, Inc.
1.7	Distributor's Address:	5165 "G" Street, Chino CA 91710 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 20108)
1.9	Business Phone / Fax:	+1 (909) 628-4707 / +1 (909) 591-8916

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia). WARNING! FLAMMABLE AEROSOL. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. <u>Classification:</u> Aerosol 2; Skin Sens. 1B; Eye Irrit. 2; <u>Hazard Statements (H):</u> H223 – Flammable aerosol. H317 – May cause an allergic skin reaction. H320 – Causes eye irritation. <u>Precautionary Statements (P):</u> P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 – Do not spray on open flame or other ignition source. P251 – Do not pierce or burn, even after use. P261 – Avoid breathing fume/gas/mist/vapors/spray. P264 – Wash hands and exposed skin areas with soap and warm thoroughly after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/eyewear. P302+P352 – IF ON SKIN: Wash with plenty warm water and soap. P333+P313 – If skin irritation or rash occurs: Get medical advice/attention. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists get medical advice/attention. P362+P364 – Take off contaminated clothing and wash it before reuse. P370+P378 – In case of fire: Use Water, Foam, CO₂, Dry Chemical, Halon (if authorized), to extinguish. P403+P235 – Store in a well-ventilated place. Keep cool. P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F). P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).</p>	 
-----	------------------------	--	---

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
AQUA (WATER/EAU)	7732-18-5	ZC0110000	231-791-2	60-100	NA	NA	NF	NF	NF	NA	NA	NA		
POLYQUATERNIUM-11	53633-54-8	NA	NA	7-13	NA	NA	NF	NF	NF	NA	NA	NA		
VP/VA COPOLYMER	25086-89-9	NA	NA	1-5	NA	NA	NF	NF	NF	NA	NA	NA		
PROPANE	74-98-6	TX2275000	200-827-9	1-5	1000	NA	1000	NF	NF	1000	NA	2100		
BUTANE	106-97-8	EJ4200000	203-448-7	1-5	1000	900	800	1900	NF	NA	NA	1900		
	75-28-5	TZ4300000	200-857-2	1-5	600	750	NF	NF	NF	NA	NA	NA		
LAURETH-4	5274-68-0	NA	226-097-1	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA		
	NA	NA	NA	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA		
PHENOXYETHANOL	122-99-6	KM0350000	204-589-7	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA		
CAPRYLYL GLYCOL	1117-86-8	NA	214-254-7	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA		
	70445-33-9	NA	408-080-2	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA		
STEARETH-21	9005-00-9	NA	NA	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA		



SAFETY DATA SHEET

Page 2 of 7
SW-1237-Z

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/5/2015

3. COMPOSITION & INGREDIENT INFORMATION – cont'd

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					ppm		ppm			ppm				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
PEG/PPG-18/18 DIMETHICONE	68037-64-9	NA	NA	0.0-1.0	NA	NA	NF	NF	NF	NA	NA	NA		
POLYSORBATE 20	9005-64-5	NA	NA	0.0-1.0	NA	NA	NF	NF	NF	NA	NA	NA		
FRAGRANCE (PARFUM)	NA	NA	NA	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA		
LIMONENE	5989-27-5	GW6360000	227-813-5	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN	
HEXYL CINNAMAL	101-86-0	GD5600000	202-983-3	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN	
	Skin Sens. 1B, Aquatic Chronic 2; H317, H411													
LINALOOL	78-70-6	NA	201-134-4	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN	
GERANIOL	106-24-1	RG5830000	203-377-1	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN	
	Skin Irrit. 2, Skin Sens. 1, Eye Dam. 1; H315, H317, H318													
CETRIMONIUM BROMIDE	57-09-0	NA	200-311-3	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA		
BUTYROSPERMUM PARKII (SHEA BUTTER)	41035-07-8	NA	NA	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA		
	Eye Irrit. 2; H319													
SODIUM PCA	28874-51-3	NA	NA	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA		
COCAMIDOPROPYL BETAINE	61789-40-0	UZ2997050	263-058-8	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA		
	Skin Irrit. 2; Eye Irrit. 2; H315, H319													
ETHYLHEXYL METHOXYCINNAMATE	5466-77-3	NA	226-775-7	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN	
HEXYLENE GLYCOL	107-41-5	SA0810000	203-489-0	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA		
KERATIN AMINO ACIDS	NA	NA	NA	0-0.1	NA	NA	NF	NF	NF	NA	NA	NA		

4. FIRST AID MEASURES

4.1	First Aid:	<p>Ingestion: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p>Eyes: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.</p> <p>Skin: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.</p> <p>Inhalation: Remove victim to fresh air at once.</p>										
4.2	Effects of Exposure:	<p>Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea.</p> <p>Eyes: Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p>Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p>Inhalation: None expected.</p>										
4.3	Symptoms of Overexposure:	Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.										
4.4	Acute Health Effects:	Moderate irritation to eyes.										
4.5	Chronic Health Effects:	No harmful or chronic health effects are expected to occur from a single accidental ingestion.										
4.6	Target Organs:	Eyes										
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system).										
		<table border="1"> <tr> <td>HEALTH</td> <td>1</td> </tr> <tr> <td>FLAMMABILITY</td> <td>3</td> </tr> <tr> <td>PHYSICAL HAZARDS</td> <td>0</td> </tr> <tr> <td>PROTECTIVE EQUIPMENT</td> <td>B</td> </tr> <tr> <td>EYES</td> <td>SKIN</td> </tr> </table>	HEALTH	1	FLAMMABILITY	3	PHYSICAL HAZARDS	0	PROTECTIVE EQUIPMENT	B	EYES	SKIN
HEALTH	1											
FLAMMABILITY	3											
PHYSICAL HAZARDS	0											
PROTECTIVE EQUIPMENT	B											
EYES	SKIN											



SAFETY DATA SHEET


Page 3 of 7
SW-1237-Z

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/5/2015

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	PRESSURIZED CONTAINER MAY BURST IF HEATED. Level 1 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Containers may rupture and release flammable liquids or/ or exposed gases if exposed to the heat of fire. Keep containers cool by spraying them with water until the fire has been extinguished. Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. When exposed to high temperatures, may produce hazardous decomposition products such as oxides of carbon (e.g., CO, CO ₂) and nitrogen (e.g., NO _x) and smoke.	
5.2	Extinguishing Methods:	Water, Foam, CO ₂ , Dry Chemical, Halon (if authorized)	
5.3	Firefighting Procedures:	As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.	


6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE). For <u>small spills</u> (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.
-----	---------	---

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Do not eat, drink, or smoke while handling this product.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans). Keep away from excessive heat and open flames.
7.3	Special Precautions:	Spilled material may present a slipping hazard if left unattended. Clean all spills promptly.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)	ACGIH		NOHSC			OSHA			OTHER	
		CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		PROPANE	1000	NA	1000	NF	NF	1000	NA	2100	
		BUTANE	1000	900	800	1900	NF	NA	NA	1900	
		ISOBUTANE	600	750	NF	NF	NF	NA	NA	NA	
		LIMONENE	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN
		HEXYCINNAMAL	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN
		LINALOOL	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN
GERANIOL	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN		
ETHYLHEXYL METHOXYCINNAMATE	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN		
8.2	Ventilation & Engineering Controls:	General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.									
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.									
8.4	Eye Protection:	Avoid eye contact. Protective eyewear recommended. Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling large quantities (of this product). Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.									



SAFETY DATA SHEET


Page 4 of 7
SW-1237-Z

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/5/2015

8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd

8.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.	
8.6	Body Protection:	No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.	

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Aerosol foam, white.
9.2	Odor:	Fragrant odor
9.3	Odor Threshold:	NA
9.4	pH:	5.5-6.5
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	NA
9.7	Flashpoint:	65 °C (149 °F)
9.8	Upper/Lower Flammability Limits:	LEL: 5.1% / UEL: 17.1% (R-152A)
9.9	Vapor Pressure:	70 ± 5 psig @ 70 °F
9.10	Vapor Density:	NA
9.11	Relative Density:	1.0 ± 0.012
9.12	Solubility in Water:	Soluble
9.13	Partition Coefficient (log Pow):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	NA
9.17	Other Information:	% solids: 3.0-4.0

10. STABILITY & REACTIVITY

10.1	Stability:	This product is stable.
10.2	Hazardous Decomposition Products:	Oxides of carbon (CO, CO ₂) and sulfur (SO ₂).
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, sparks and high heat.
10.5	Incompatible Substances:	None known.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	The product has not been tested for specific toxicity data.		
11.3	Acute Toxicity:	See section 4.4		
11.4	Chronic Toxicity:	See section 4.5		
11.5	Suspected Carcinogen:	No.		
11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 4.3.		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	There is no specific data available for this product.
12.2	Effects on Plants & Animals:	There is no specific data available for this product.
12.3	Effects on Aquatic Life:	There is no specific data available for this product.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Waste disposal must be in accordance with appropriate Federal, state, and local regulations.
13.2	Special Considerations:	U.S. EPA Waste Number: D001 (characteristic - ignitable).



SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/5/2015

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1000 mL) – until 12/31/2020 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1000 mL)	
14.2	IATA (AIR):	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 500 mL) UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 500 mL)	
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1000 mL)	
14.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1000 mL) or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE"	
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1000 mL)	
14.6	SCT (MEXICO):	UN1950, AEROSOLS, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1000 mL)	
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1000 mL)	

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	NA	
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics). This material does not contain any hazardous air pollutants. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA.	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B5, D2B (Flammable Aerosol, Other Toxic Effects)	
15.7	State Regulatory Information:	<u>Propane</u> is found on the following state criteria list: Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List (WA). <u>Isobutane</u> is found on the following state criteria list: MA, NJ and PA. <u>Hexylene Glycol</u> is found on the following state criteria list: FL, MA, MN, PA and WA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).	
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC. <u>Isobutane</u> : Flammable (F+). <u>Risk Phrases</u> (R): 12 – Extremely flammable. <u>Safety Phrases</u> (S): 2-6-16-53-45 – Keep out of reach of children. Keep cool store below 120 °F (48.8 °C). Keep away from sources of ignition – No smoking. Avoid exposure – obtain special instructions before use. In case of accident or if you fell unwell seek medical advice immediately. Flammable (F). <u>Risk Phrases</u> (R): 11 – Flammable. <u>Safety Phrases</u> (S): 2-7-16-24/25 – Keep out of reach of children. Keep container tightly closed. Keep away from sources of ignition – No smoking. Do not breathe vapor. Avoid contact with skin and eyes. <u>Hexylene Glycol</u> : Irritant (Xi). <u>Risk Phrases</u> (R): 36/38 – Irritating to eyes and skin. <u>Safety Phrases</u> (S): 2 -26 - 2-26 – Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	



SAFETY DATA SHEET



Page 6 of 7
SW-1237-Z

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/5/2015

16. OTHER INFORMATION

16.1	Other Information:	WARNING! FLAMMABLE AEROSOL. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing fume/gas/mist/vapours/spray. Wash hands and exposed skin areas with soap and warm thoroughly after handling. If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN: Wash with plenty warm water and soap. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advice/attention. In case of fire: Use Water, Foam, CO ₂ , Dry Chemical, Halon (if authorized) to extinguish. Store in a well-ventilated place. Keep cool. Use only as directed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F). Discontinue use immediately if irritation develops. KEEP OUT OF REACH OF CHILDREN.	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Shield Packaging of CA's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and NO WARRANTIES OF ANY TYPE, EXPRESSED OR IMPLIED, ARE PROVIDED INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	Shield Packaging of CA, Inc. 5165 "G" Street Chino CA 91710 USA Tel: +1 (909) 628-4707 Fax: +1 (909) 591-8916 http://www.shieldpackaging.com	
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	 <i>Dangerous Goods Training & Consulting</i>



SAFETY DATA SHEET

Page 7 of 7
SW-1237-Z

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 5/5/2015

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
C	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD ₀₁	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD ₀₁ , LD ₀₁ & LD ₅₀ or TC, TC ₀₁ , LC ₀₁ , & LC ₅₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment

PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
mg/m ³	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source